Package: tflow (via r-universe)

October 15, 2026

Title Setup a project in the tflow style for using the targets package

Version 0.4.1

Description Has a function that sets up an R workflow in the dflow style, using targets.

Depends R (>= 3.5.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports usethis, fnmate, glue, readr, cli, rstudioapi, sourcetools, atcursor (>= 0.0.1), fs, yaml

Suggests conflicted, capsule, dotenv, targets, tarchetypes, withr, here

Remotes milesmcbain/fnmate, milesmcbain/capsule, milesmcbain/atcursor

RoxygenNote 7.2.3

Config/pak/sysreqs cmake git make libgit2-dev libuv1-dev libssl-dev libx11-dev

Repository https://milesmcbain.r-universe.dev

Date/Publication 2025-06-26 23:36:55 UTC

RemoteUrl https://github.com/milesmcbain/tflow

RemoteRef master

RemoteSha 7a4e72bd8e88eb7a83402572b389fcf0507c365c

Contents

qmd_target 2
rmd_target 2
use_gitignore 3
use_qmd 3
use_rmd 4
use_tflow 4

Index **5**

qmd_target *qmd_target*

Description

Generate a target for a Quarto file

Usage

```
qmd_target(target_name)
```

Arguments

target_name	of a target to generate qmd target for.

Value

target text to the console.

Author(s)

Robert M Flight

rmd_target *rmd_target*

Description

Generate a target for an R markdown file

Usage

```
rmd_target(target_name)
```

Arguments

target_name	of a target to generate rmd target for.

Value

target text to the console.

Author(s)

Miles McBain

use_gitignore *use_gitignore*

Description

Use a starter .gitignore

Usage

```
use_gitignore()
```

Details

Drop a starter .gitignore in the current working directory, including ignores for targets and capsule (renv).

Value

nothing, creates a file.

Author(s)

Miles McBain

use_qmd *use_qmd*

Description

Create a Quarto file and generate target definition code.

Usage

```
use_qmd(target_name)
```

Arguments

target_name	a name for target and the generated quarto document.

Details

The generated document defaults to the "./doc" folder. This can be overridden with option 'tflow.report_dir'.

Value

the path of the file created. (invisibly)

Author(s)

Robert M Flight

`use_rmd` *use_rmd*

Description

Create an RMarkdown file and generate target definition code.

Usage

```
use_rmd(target_name)
```

Arguments

`target_name`	a name for target and the generated R markdown document.

Details

The generated document defaults to the "./doc" folder. This can be overridden with option 'tflow.report_dir'.

Value

the path of the file created. (invisibly)

Author(s)

Miles McBain

`use_tflow` *use_tflow*

Description

Setup a tflow project

Usage

```
use_tflow()
```

Details

Creates files and directories according to the tflow template.

Value

Nothing. Modifies your workspace.

Index

qmd_target, 2

rmd_target, 2

use_gitignore, 3
use_qmd, 3
use_rmd, 4
use_tflow, 4