

Package: tflow (via r-universe)

July 26, 2024

Title Setup a project in the tflow style for using the targets package

Version 0.4.1

Description Has a function that sets up an R workflow in the dflow style, using targets.

Depends R (>= 3.5.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports usethis, fnmate, glue, readr, cli, rstudioapi, sourcetools, atcursor (>= 0.0.1), fs, yaml

Suggests conflicted, capsule, dotenv, targets, tarchetypes, withr, here

Remotes milesmbain/fnmate, milesmbain/capsule, milesmbain/atcursor

RoxygenNote 7.2.3

Repository <https://milesmbain.r-universe.dev>

RemoteUrl <https://github.com/milesmbain/tflow>

RemoteRef master

RemoteSha 237a7c199d8833c7174327211c45fbb57a17a664

Contents

qmd_target	2
rmd_target	2
use_gitignore	3
use_qmd	3
use_rmd	4
use_tflow	4

Index	5
--------------	----------

qmd_target

qmd_target

Description

Generate a target for a Quarto file

Usage

```
qmd_target(target_name)
```

Arguments

`target_name` of a target to generate qmd target for.

Value

target text to the console.

Author(s)

Robert M Flight

rmd_target

rmd_target

Description

Generate a target for an R markdown file

Usage

```
rmd_target(target_name)
```

Arguments

`target_name` of a target to generate rmd target for.

Value

target text to the console.

Author(s)

Miles McBain

use_gitignore	<i>use_gitignore</i>
---------------	----------------------

Description

Use a starter .gitignore

Usage

```
use_gitignore()
```

Details

Drop a starter .gitignore in the current working directory, including ignores for targets and capsule (renv).

Value

nothing, creates a file.

Author(s)

Miles McBain

use_qmd	<i>use_qmd</i>
---------	----------------

Description

Create a Quarto file and generate target definition code.

Usage

```
use_qmd(target_name)
```

Arguments

target_name a name for target and the generated quarto document.

Details

The generated document defaults to the `"/doc"` folder. This can be overridden with option `'tflow.report_dir'`.

Value

the path of the file created. (invisibly)

Author(s)

Robert M Flight

use_rmd	<i>use_rmd</i>
---------	----------------

Description

Create an RMarkdown file and generate target definition code.

Usage

```
use_rmd(target_name)
```

Arguments

target_name a name for target and the generated R markdown document.

Details

The generated document defaults to the `"/doc"` folder. This can be overridden with option `'tflow.report_dir'`.

Value

the path of the file created. (invisibly)

Author(s)

Miles McBain

use_tflow	<i>use_tflow</i>
-----------	------------------

Description

Setup a tflow project

Usage

```
use_tflow()
```

Details

Creates files and directories according to the tflow template.

Value

Nothing. Modifies your workspace.

Index

qmd_target, 2

rmd_target, 2

use_gitignore, 3

use_qmd, 3

use_rmd, 4

use_tflow, 4